

MAGIC

TECHNICAL SPECIFICATIONS :



INPUT	- 175V-285V
OUTPUT	- 230 V ± 4% (TYPICAL)
CORRECTION RATE	- 500V / SEC.
RESPONSE TIME	- 1/2 CYCLE(10ms)
FREQUENCY	- 47Hz TO 53 Hz
OVERLOAD CAPACITY	- 130% FOR 60 Sec.
EFFICIENCY	- > 95%
HARMONIC DISTORTION	- NIL
PROTECTIONS	- SOFT TURN ON DELAY.
	- COMPLETE SURGE SUPPRESSION.
	- OVERLOAD BY FUSE.
	- HIGH/LOW CUT OUTPUT
	- EARTHING STATUS INDICATION
BOX SIZE	- L 215mm • W 110mm • H 135mm
CAPACITY	- 250 V,350 VA, 500VA.

SLEEK

TECHNICAL SPECIFICATIONS : WITH 'MAGIC' FEATURE



INPUT	- 170V-300 V
OUTPUT	- 230 ± 4 (TYPICAL)
EFFICIENCY	- > 97%
*POWER FACTOR IMPROVEMENT CIRCUITRY.	
SIZE	- L 205mm • W140mm • H 185mm
CAPACITY	- 500VA,750VA,

REGULAR

TECHNICAL SPECIFICATIONS : WITH 'SLEEK' FEATURES



INPUT	- 175V-295V
OUTPUT	- 230 ± 4% (TYPICAL)
METERING	- INPUT/OUTPUT VOLTAGE
* CONTROL CIRCUITRY IS TOTALLY ISOLATED TO OUTPUT POWER CIRCUITS.	
SIZE	- L 285mm • W200mm • H 145mm
CAPACITY	- 500VA,750VA,1000VA

INDUSTRIAL

TECHNICAL SPECIFICATIONS : WITH 'REGULAR' FEATURES



INPUT	- 170V-300 V
OUTPUT	- 230 ± 4%
* BUCK BOOST PRINCIPLE	
PROTECTIONS	- SHORT CIRCUIT BY 'MCB'
SIZE	- L 300mm • W 225mm • H 215mm
CAPACITY	- 2KVA TO5KVA.